

Industry Supplies Silanodur HD

EAN: 4260531330861

Art. no.: bis-sildur-290t



High-performance elastic MS-polymer adhesive for crystal-clear bonds.

Adhesive and sealant for mounting and fastening a wide variety of materials.

Properties:

- paintable / overcoatable with all water-based paints
- for indoor and outdoor use in all weather conditions
- no bubble formation on porous substrates
- fast curing, even at low temperatures
- isocyanate-, silicone- and solvent-free
- excellent adhesion to most substrates, even damp ones
- almost odorless and weather-resistant
- low-shrinkage curing, permanently elastic and aging-resistant
- suitable for sealing & bonding

Areas of application:

Bonding/sealing of bare and painted metal, ceramics & glass, natural stone, wood and wood-based materials, plastics (except PE, PP, PTFE & silicone), cement- and gypsum-bound materials

Construction industry: bonding/sealing of tiles, parquet, wood, wet rooms (bathroom/kitchen)

Vehicle industry: bonding/sealing of composite material, sandwich panels, metal components, etc.

Contents (cartridge) & weight	290 ml in cartridge 383g
Color:	transparent
Skin formation:	approx. 10 minutes
Curing at 55% humidity	Approx. 2 mm in 24 h at +23°C
Elongation at break & density:	250 % 1.05 g/ml
Tensile strength & Shore A	2.4 MPa 45
Temperature resistance:	-40 to +100 °C
Processing temperature:	+5 to +40 °C
Customs tariff number	32141010
Areas of application	Automotive, construction, industry, factory/facility, Rail, aerospace & marine

Safety data sheet according to Regulation 1907/2006 available.

Prices on request. Manufacturer's information. Subject to change. This datasheet is protected by copyright and may not be reproduced, copied or altered, in whole or in part, without the prior consent of Brado GmbH.